



Wilkinson Hi-Rise

3001 GREENE STREET
HOLLYWOOD, FL 33020
PHONE: (800) 231-3888 FAX: (954) 342-4338

“Dual Door” Trash Chute Guillotine Replacement



OPEN POSITION (STANDARD SETTING)
Both Doors Are In Open Position

CLOSED POSITION (@ CONTAINER CHANGING)
Manual Door Only Is Closed Using Handle
Fusible Link Does Not Have To Be Removed!

When Is It Time To Replace Your Trash Chute Guillotine?

The trash chute fire discharge assembly must be held open by a current year UL approved fusible link and the assembly must be tested at least once per year for self closure in the event of a fire melting the fusible link. The “guillotine” requires replacement when any of the following conditions exist:

- Sliding blade is bent out of position and will not self close
- Steel frame is bent not allowing sliding blade to self close
- Rust has “frozen” the blade in the tracks of the frame

The life cycle of a trash chute fire discharge assembly or sometimes called “guillotine” requires maintenance when any of the following conditions exist:

- Fusible link has broken or has corroded or oxidized
- Frame assembly is not secured tightly to the trash chute
- Spring assemblies have become rusted or have broken entirely and will not pull
- Roller wheel assemblies have become rusted or broken and will not roll smoothly

DON'T WAIT UNTIL THE FIRE INSPECTOR ISSUES YOUR PROPERTY A VIOLATION! You're your regional Wilkinson Hi-Rise representative today for a free inspection and estimate!